

**LISTING OF CLAIMS:**

Please amend the claims as follows:

- 1 1. (Original) A method for displaying a quality of a wireless transmission comprising:  
2 receiving the wireless data transmission wherein the wireless data transmission originates  
3 from multiple transmit antennae;  
4 determining the quality of the wireless data transmit signal based on a quality parameter  
5 of the wireless transmission; and  
6 displaying the quality of the wireless data transmission.
- 1 2 (Original) The method of claim 1 wherein the wireless data transmission comprises multiple  
2 streams of data and determining the quality of the wireless data transmission based on a quality  
3 parameter of the wireless data transmission comprises:  
4 determining a value of the quality parameter for each of the multiple streams of data.
- 1 3. (Original) The method of claim 1 wherein the wireless data transmission comprises multiple  
2 streams of data and determining the quality of the wireless data transmission based on a quality  
3 parameter of the wireless transmission comprises:  
4 determining an aggregate value of the quality parameter for the multiple streams of data.
- 1 4. (Original) The method of claim 2 wherein the quality parameter is selected from a group  
2 consisting of bit error rate, packet error rate and a frame error rate.
- 1 5. (Original) The method of claim 3 wherein the quality parameter is selected from a group  
2 consisting of bit error rate, packet error rate and a frame error rate.
- 1 6. (Original) The method of claim 2 wherein the quality parameter is selected from a group  
2 consisting of a signal-to-noise ration, a carrier-to-interference ratio and a signal-to-interference  
3 plus noise ratio.

1 7. (Original) The method of claim 3 wherein the quality parameter is selected from a group  
2 consisting of a signal to noise ratio, a carrier to interference ratio and a signal to interference plus  
3 noise ratio.

1 8. (Original) The method of claim 2 wherein the quality parameter comprises the number of  
2 cyclic redundancy check failures.

1 9. (Original) The method of claim 3 wherein the quality parameter comprises the number of  
2 cyclic redundancy check failures.

1 10. (Original) The method of claim 1 wherein the wireless data transmission comprises multiple  
2 streams of data and determining the quality of the wireless data transmission based on a quality  
3 parameter of the wireless data transmission comprises:  
4 determining a propagation channel for the wireless data transmission; and  
5 determining a value for the quality parameter based on the propagation channel.

1 11. (Original) The method of claim 10 wherein the quality parameter is selected from a group  
2 consisting of a bit error rate of each of the multiple streams of data, a packet error rate of each of  
3 the multiple streams of data, a frame error rate of each of the multiple streams of data.

1 12. (Original) The method of claim 10 wherein the quality parameter is selected from a group  
2 consisting of a bit error rate of the multiple streams of data, a packet error rate of the multiple  
3 streams of data, a frame error rate of the multiple streams of data.

1 13. (Original) The method of claim 10 wherein the quality parameter is selected from a group  
2 consisting of signal-to-noise ratio of each of the multiple streams of data, a carrier-to-noise ratio  
3 of each of the multiple streams of data, and a signal-to-interference plus noise ratio of each of the  
4 multiple streams of data.

1 14. (Original) The method of claim 10 wherein the quality parameter is selected from a group  
2 consisting of signal-to-noise ratio of the multiple streams of data, a carrier-to-noise ratio of the

3 multiple streams of data, and a signal-to-interference plus noise ratio of the multiple streams of  
4 data.

1 15. (Original) The method of claim 10 wherein the quality parameter is selected from a group  
2 consisting of a channel condition number, a delay spread, a time variance, and a frequency  
3 variance.

1 *Please cancel claims 16-45, without prejudice.*

1 46. (Currently Amended) An apparatus for displaying [the] a quality of a wireless data  
2 transmission comprising:  
3 means for receiving the wireless data transmission wherein the wireless data transmission  
4 originates from multiple transmit antennae;  
5 means for determining the quality of the wireless data transmission based on a quality  
6 parameter of the wireless data transmission; and  
7 means for displaying the quality of the wireless data transmission.

1 47. (Original) The apparatus of claim 46 wherein the wireless data transmission comprises  
2 multiple streams of data and the means for determining the quality of the wireless data  
3 transmission based on a quality parameter of the wireless data transmission further comprises:  
4 means for determining a value of the quality parameter for each of the multiple streams  
5 of data transmission.

1 48. (Original) The apparatus of claim 46 wherein the means for determining the quality of the  
2 wireless data transmission based on a quality parameter of the wireless data transmission further  
3 comprises:  
4 means for determining an aggregate value of the quality parameter for the multiple  
5 streams of data.

1 49. (Original) The apparatus of claim 47 wherein the means for displaying the quality of the  
2 wireless transmission comprises means for displaying the value.

## BEST AVAILABLE COPY

1 50. (Original) The apparatus of claim 48 wherein means for displaying the quality of the  
2 wireless transmission comprises means for displaying the aggregate value.

1 51. (Original) The apparatus of claim 49 wherein the means for displaying the value comprises  
2 LED indicators.

1 52. (Original) The apparatus of claim 49 wherein the means for displaying the value comprises  
2 an analog meter.

1 53. (Original) The apparatus of claim 50 wherein the means for displaying the value comprises  
2 separate sets of LED indicators wherein each of the separate sets of LED indicators corresponds  
3 to each of the multiple streams of data.

1 54. (Original) The apparatus of claim 50 wherein the means for displaying the aggregate value  
2 comprises an analog meter.

1 55. (Currently Amended) The apparatus of claim 49 wherein the quality parameter comprises  
2 a channel quality parameter and a data quality parameter and the means for displaying the value  
3 of the quality parameter comprises a first and second analog meter wherein the first analog meter  
4 displays [the] a value of the channel quality parameter and the second analog meter displays  
5 [the] a value of the data quality parameter.

1 56. (Currently Amended) The apparatus of claim 49 wherein the quality parameter comprises  
2 a channel quality parameter and a data quality parameter and the means for displaying the value  
3 of the quality parameter comprises a first and second set of LED indicators wherein the first set  
4 of LED indicators corresponds to the channel quality parameter and the second set of [Led] LED  
5 indicators corresponds to the data quality parameter.

1 *Please cancel claims 57-73, without prejudice.*

1 *Please add the following new claims:*

1 74. (New) A method according to claim 1, wherein the multiple streams comprising the  
2 wireless data transmission are received via two or more receive antennae.

1 75. (New) An apparatus according to claim 49, further comprising:  
2 two or more receive antennae through which the means for receiving receives multiple  
3 streams of the wireless transmission.

1 76. (New) An apparatus comprising:  
2 a receiver, to receive a wireless transmission wherein the wireless transmission originates  
3 from multiple transmit antennae; and  
4 a quality display unit, responsive to if not embedded within the receiver, to determine a  
5 quality of the received wireless data transmission based, at least in part, on an ascertained one or  
6 more quality parameter(s) associated with the wireless data transmission, and to provide a  
7 display of such quality of the wireless data transmission.

1 77. (New) An apparatus according to claim 76, the quality display unit comprising:  
2 a quality indicator processor, responsive to a channel estimator in the receiver, to  
3 determine a quality of the received wireless data transmission.

1 78. (New) An apparatus according to claim 77, the quality display unit comprising:  
2 a display, responsive to the quality indicator processor, to display the quality of the  
3 wireless data transmission.

1 79. (New) An apparatus according to claim 76, wherein the wireless transmission is  
2 comprised of a multiple spatial streams.

1 80. (New) An apparatus according to claim 79, the quality display unit to determine a quality  
2 value for each of the multiple spatial streams and to display at least a subset of the determined  
3 quality values.

- 1 81. (New) An apparatus according to claim 79, the quality display unit to display a  
2 representation of a mathematical combination of the determined quality values for each of the  
3 multiple spatial streams.
- 1 82. (New) An apparatus according to claim 76, further comprising:  
2 two or more receive antennae through which the receiver receives the wireless  
3 transmission.
- 1 83. (New) An apparatus according to claim 76, wherein the determined quality comprises a  
2 channel quality parameter and a data quality parameter, the quality display unit including a first  
3 and second set of indicators, wherein the first set of indicators to display a representation of the  
4 channel quality parameter and the second set of indicators to display a representation of the data  
5 quality parameter.
- 1 84. (New) A system comprising:  
2 two or more antennae responsive to a wireless transmission;  
3 a receiver, responsive to the two or more antennae, to receive a wireless transmission  
4 wherein the wireless transmission originates from multiple transmit antennae, to determine a  
5 quality of the received wireless data transmission based, at least in part, on an ascertained one or  
6 more quality parameter(s) associated with the wireless data transmission; and  
7 a display, responsive to the receiver, to provide a display of such quality of the wireless  
8 data transmission.
- 1 85. (New) A system according to claim 84, wherein the wireless transmission is comprised  
2 of a multiple spatial streams.
- 1 86. (New) A system according to claim 85, the receiver to determine a quality value for each  
2 of the multiple spatial streams and to display at least a subset of the determined quality values.

1 87. (New) A system according to claim 85, the receiver to display a representation of a  
2 mathematical combination of the determined quality values for each of the multiple spatial  
3 streams.

1 88. (New) A system according to claim 84, wherein the determined quality comprises a  
2 channel quality parameter and a data quality parameter, the quality display unit including a first  
3 and second set of indicators, the first set of indicators to display a representation of the channel  
4 quality parameter and the second set of indicators to display a representation of the data quality  
5 parameter.